

The HSA-410WD offers the fastest available Vertical Shrink Sleeve Labeling and Tamper Banding. Its proven design has become the go-to shrink sleeve applicator for customers that need maximum versatility.

Tripack HSA-410WD shrink label applicators are built for handling high-speed applications, extensive line integration requirements, and heavy production schedules. These applicators are built to last, with rugged stainless steel and aluminum construction, with servo-motion film handling.

Tripack's mandrel-based delivery ensures the highest level of operational efficiency and precise sleeve placement. Easy-to-operate touch-screens are powered by Allen-Bradley control systems and servo-motion.

BENEFITS

- Eight-point mandrel/bullet design film delivery system with pre-form lower options based on container shape and size. Pre-calibrated clutch wheels for PERFECT mandrel placement and pressure tension.
- Servo-driven, high speed film delivery and multi-blade knife assembly
 - Tool-less (quick-change) knife assembly
- Powered film assist assembly with ZERO tension film web design
- Film loading/unwind station for 5" or 10" Core/19" Film OD
- Stainless steel, fall through clean design, frame with caster wheels and adjustable feet
 - Locks into place with new or existing conveyor
- Integrated dual timing screw assembly
- Washdown ready
- Allen-Bradley Control System:
 - Cantilever style design capable of running over existing conveyors
 - CompactLogix PLC
 - Color Touch Screen HMI
 - Recipe-driven sizes for change-over convenience
 - Kinetix Servo Drives
 - Stack light with multiple warning lights and audible alarms



STANDARD SPECIFICATIONS

Max. Speed:	500 ppm
Product Range:	1-10" Diameter
Layflat Range:	40-400 mm
Cut Length Range:	30-330 mm

SHRINK APPLICATIONS



PRIMARY SLEEVE



FULL BODY OVER-THE-CAP SLEEVE



TAMPER EVIDENT BAND



PARTIAL BODY SLEEVE



MULTI-PACK SLEEVE



WIDE CONTAINER SLEEVE