



HSA-405

- Eight-point mandrel/bullet design film delivery system with pre-form lower options based on container shape and size. Pre-calibrated clutch wheels for PERFECT mandrel placement and pressure tension
- Allen Bradley touchscreen HMI with recipe-driven sizes for change-over convenience
- Stainless-steel frame locks into place with new or existing conveyor
- Stack light with multiple warning lights and audible alarm
- Powered film assist assembly with ZERO tension film web design
- Allen Bradley servo-driven, High speed film delivery and multi-blade knife assembly
- Quick-change toolless knife assembly
- Film loading/unwind station for 5" or 10" Core/19" Film OD
- Cantilever style head capable of running over existing conveyors with fully guarded framing
- Stainless-steel frame with caster wheels and adjustable feet

Max. Speed:	400 ppm
Product Range:	1-10" Diameter
Layflat Range:	40-400 mm
Cut Length Range:	30-250 mm



HSA-410T

- Eight-point mandrel/bullet design film delivery system with pre-form lower options based on container shape and size. Pre-calibrated clutch wheels for PERFECT mandrel placement and pressure tension
- Allen Bradley touchscreen HMI with recipe-driven sizes for change-over convenience
- Stainless-steel frame locks into place with new or existing conveyor
- Stack light with multiple warning lights and audible alarm
- Powered film assist assembly with ZERO tension film web design
- Allen Bradley servo-driven, High speed film delivery and multi-blade knife assembly
- Quick-change toolless knife assembly
- Integrated dual-timing screw assembly
- Stainless-steel frame with caster wheels and adjustable feet

Max. Speed:	800 ppm
Product Range:	1-3.5" Diameter
Layflat Range:	40-140 mm
Cut Length Range:	30-250 mm