



## ST-1 or ST- 2

- Heat-safe baffle pressure calibration compartments
- Cantilever/conveyor through tunnel design
- Adjustable stainless-steel weldment frame with adjustable feet
- Variable speed steam exhaust controls
- Pressure-reducing valve including pressure and temperature gauges
- Independent and adjustable steam baffles with optional toolless adjustment
- Water collection tray with drain system

|                        |                |                |
|------------------------|----------------|----------------|
|                        | <b>ST-1-45</b> | <b>ST-1-75</b> |
| <b>Length:</b>         | 6.5'           | 6.5'           |
| <b>Tunnel Opening:</b> | 6.3 x 25"      | 9.5 x 25"      |
|                        | <b>ST-2-45</b> | <b>ST-2-75</b> |
| <b>Length:</b>         | 10'            | 10'            |
| <b>Tunnel Opening:</b> | 6.3 x 25"      | 9.5 x 25"      |



## ST-3

- Heat-safe baffle pressure calibration compartments
- Cantilever/conveyor through tunnel design
- Adjustable stainless-steel weldment frame with adjustable feet
- Variable speed steam exhaust controls
- Pressure-reducing valve including pressure and temperature gauges
- Independent and adjustable steam baffles with optional toolless adjustment
- Water collection tray with drain system

|                        |                |                |
|------------------------|----------------|----------------|
|                        | <b>ST-3-45</b> | <b>ST-3-75</b> |
| <b>Length:</b>         | 3'             | 3'             |
| <b>Tunnel Opening:</b> | 6.3 x 25"      | 9.5 x 25"      |