



TE-150

- Film loading/ unwind station for 5" Core /15.5" Film OD
- Guillotine Knife Assembly
- Extruded aluminum frame locks into place with new or existing conveyor
- Caster wheels and adjustable feet
- Stack light with multiple warning lights and audible e-stop
- Mandrel / Butterfly film delivery system
- Touchscreen HMI with recipe driven sizes for change over convenience
- Cantilever style head capable of running over existing conveyor lines with adjustable head height feature

Max. Speed:	120 ppm
Product Range:	1-3.75" Diameter
Layflat Range:	40-170 mm
Cut Length Range:	25-50 mm
TAMPER BANDING ONLY	



LSA-160

- Powered operator side film loading/ unwind station for 5" Core /15.5" Film OD
- Servo Driven, Multi Blade Knife Assembly
- Extruded aluminum frame locks into place with new or existing conveyor
- Caster wheels and adjustable feet
- Stack light with multiple warning lights and audible alarm
- Mandrel design film
- Touchscreen HMI with recipe driven sizes for change over convenience
- Cantilever style head capable of running over existing conveyor lines with adjustable head height feature

Max. Speed:	100 ppm
Product Range:	1-4.25" Diameter
Layflat Range:	40-170 mm
Cut Length Range:	50-250 mm